



P3.91 * P7.8 mm 70% Transparent Led Display

Model No.: **P391T**

Cabinet Pics



Module Parameter

Pixel Pitch	P3.91 horizontal * P7.81 Vertical	
Pixel Configuration	SMD1921	
Density	32,256 pixels/m²	
Module Resolution	128pixel(L) * 16pixel(H)	
Module Dimension	500mm(L) * 125mm(H)	
Driving Mode	Constant current, 1/7 duty	
Module Transmittance	70%	

LED Cabinet

Module Quantity in a Cabinet	2(L) * 2(H)
Cabinet Dimension	1000(L) * 500 (H) * 50(D)mm
Cabinet Resolution	256(L) * 64 (H)
Cabinet Material	Aluminum Diecast
Cabinet Weight	≈7Kg

Santander 2069, Colonia Santa Monica CP 44220 Guadalajara Jalisco Mexico
Tels. 3318945034, 333-98-3333 , 331-342-2632,

Reliability	
Working Temperature	-20~+60 °C
Storage Temperature	-30~+70 °C
Working Humidity	10%~90% RH
Lifetime	100,000 hours
MTBF	5000 hours
Continuous Operating Time	≥72 hours
Protection Grade	IP43
Control System	
Frame Frequency	≥60Hz
Refresh Frequency	1920Hz
Input Signal	Network protocol RJ45
Control Distance	100m(Ethernet cable);
Electricity Parameter	
Brightness	5,000 nits m ²
Viewing Angle	140°(Horizontal); 140°(Vertical)
Best Viewing Distance	≥3m
Gray Grade	14 bits
Display Color	4.4 trillion Colors
Protocol	NOVA
Operation Power	AC100-240V 50-60Hz
Max. Power Consumption	730 W/m ²
Avg. Power Consumption	200W/m ²

Santander 2069, Colonia Santa Monica CP 44220 Guadalajara Jalisco Mexico
Tels. 3318945034, 333-98-3333 , 331-342-2632,